
COPYRIGHT GENERAL ELECTRIC CO.

FORMAT: USA MATERIAL SAFETY DATA SHEET PRODUCT: GE012 RTV SILICONE RUBBER SEALANT

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: SUPPLIED BY: INACTIVE INACTIVE

EMERGENCY PHONE (24 HRS) EMERGENCY PHONE (24 HRS)

.

REVISED: 04/01/01 PREPARER: JL MCGUFFEY

CHEMICAL FAMILY/USE: SILICONE RUBBER SEALANT

FORMULA: MIXTURE

2. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION/ APPROX. ACGIH TLV OSHA PEL CAS REG NO. WGT. % TWA STEL TWA STEL UNITS

1. HAZARDOUS

METHYLTRIACETOXYSILANE

4253-34-3 1-5 10(R) NE 10(R) NE PPM

2. NON-HAZARDOUS

POLYDIMETHYLSILOXANE SILANOL/STPD

70131-67-8 60-80 - NE - NE -

SILANOL/STPD SILOXANE W/ME SILSQXNS

68554-67-6 5-10 NF NE NF NE NA

TREATED FUMED SILICA

68611-44-9 5-10 10 NE 15 NE MG/M3

See Section 15 for description of any WHMIS Trade Secret(s).

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

This section not in use

POTENTIAL HEALTH EFFECTS:

INGESTION:

May be harmful if swallowed.

SKIN CONTACT:

Uncured product contact will irritate lips, gums and tongue.

Uncured product contact may irritate the skin.

INHALATION:

Causes irritation of the mouth, nose, and throat.

Applies only in uncured state.

EYE CONTACT:

Uncured product contact irritates eyes.

MEDICAL CONDITIONS AGGRAVATED:

None known.

SUBCHRONIC (TARGET ORGAN) EFFECTS:

None known

CHRONIC EFFECTS/CARCINOGENICITY:

This product or one of its ingredients present 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by

NTP, IARC, or OSHA. PRODUCTS/INGREDIENTS

This space reserved for special use.

PRINCIPLE ROUTES OF EXPOSURE:

Dermal - skin.

Inhalation.

OTHER:

Acetic acid released during curing.

This product contains Methylpolysiloxanes which can generate Formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. An MSDS for Formaldehyde is available from GE Silicones.

4. FIRST AID MEASURES

INGESTION:

Rinse mouth with water several times.

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.

Get medical attention if irritation persists.

INHALATION:

Move person to fresh air.

EYES:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN:

None known.

.-----

5. FIRE FIGHTING MEASURES

FLASH POINT: NA (C) NA (F)

METHOD : NA IGNITION TEMP : UNK (C) UNK (F)

IGNITION TEMP : UNK (
FLAMMABLE LIMITS IN AIR - LOWER (%): UNK
FLAMMABLE LIMITS IN AIR - UPPER (%): UNK SENSITIVITY TO MECHANICAL IMPACT (Y/N): NO

SENSITIVITY TO STATIC DISCHARGE:

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA:

All standard firefighting media SPECIAL FIREFIGHTING PROCEDURES:

None known.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Wipe, scrape or soak up in an inert material and put in a container for disposal.

Wash walking surfaces with detergent and water to reduce slipping hazard.

Wear proper protective equipment as specified in the protective equipment section.

Increase area ventilation.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container closed when not in use.

Avoid contact with skin and eyes.

Use only in a well ventilated area.

Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation.

Product releases acetic acid during application and curing. Use mechanical ventilation to stay below TLV of 10 ppm acetic acid.

Uncured product contact irritates eyes.

Uncured product contact may irritate skin.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Exhaust ventilation Eyewash stations.

Use in a well ventilated area. RESPIRATORY PROTECTION: Use in a well ventilated area. Use approved NIOSH respiratory protection if TLV exceeded or overexposure is likely. PROTECTIVE GLOVES: Cloth gloves. EYE AND FACE PROTECTION: Safety glasses. OTHER PROTECTIVE EQUIPMENT: None known. VENTILATION: Use only in well ventilated area.

9. PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT INFORMATION:
BOILING POINT : NA (C) NA (F)
VAPOR PRESSURE(20 C) (MM HG): NA
VAPOR DENSITY (AIR=1) : NA
FREEZING POINT : NA (C) NA (F)
MELTING POINT : NA (C) NA (F)
PHYSICAL STATE : SOLID
ODOR : ACETIC ACID
COLOR : TRANSLUCENT
ODOR THRESHOLD (PPM) : UNK
% VOLATILE BY VOLUME : <3.9
EVAP. RATE(BUTYL ACETATE=1): <1
SPECIFIC GRAVITY (WATER=1) : 1.04
DENSITY (KG/M3) : 1040 1040 DENSITY (KG/M3) ACID/ALKALINITY (MEQ/G) : NA NA PН

VOC EXCL.H20 & EXEMPTS(G/L): <41
SOLUBILITY IN WATER (20 C): INSOLUBLE

SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT): TOLUENE

10. STABILITY AND REACTIVITY

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

10 HAZARDOUS THERMAL DECOMPOSITION/COMBUSTION PRODUCTS:

Carbon monoxide. Carbon dioxide. Silicon dioxide. Acetic acid.

INCOMPATIBILITY (MATERIALS TO AVOID):

None known.

CONDITIONS TO AVOID:

None known.

11. TOXICOLOGICAL INFORMATION	
METHYLTRIACETOXYSILANE ACUTE ORAL LD50 (MG/KG): 2,060 (RAT) ACUTE DERMAL LD50 (MG/KG): NONE FOUND ACUTE INHALATION LC50 (MG/L): NONE FOUND OTHER: None.	
AMES TEST:	
POLYDIMETHYLSILOXANE SILANOL/STPD ACUTE ORAL LD50 (MG/KG): >40000 RAT ACUTE DERMAL LD50 (MG/KG): NON-IRRITATING RBT ACUTE INHALATION LC50 (MG/L): >535 RAT OTHER: None.	
AMES TEST:	
SILANOL/STPD SILOXANE W/ME SILSQXNS ACUTE ORAL LD50 (MG/KG): >40,000 RAT,ESTM. ACUTE DERMAL LD50 (MG/KG): NONE FOUND ACUTE INHALATION LC50 (MG/L): >535 MG/L ESTM. OTHER: None.	
AMES TEST:	
TREATED FUMED SILICA ACUTE ORAL LD50 (MG/KG): >10,000MG/KG (RAT) ACUTE DERMAL LD50 (MG/KG): NA ACUTE INHALATION LC50 (MG/L): NA OTHER: None.	
10 AMES TEST:	
12. ECOLOGICAL INFORMATION	
ECOTOXICOLOGICAL INFORMATION: No data at this time CHEMICAL FATE INFORMATION: No data at this time	
13. DISPOSAL CONSIDERATIONS	

DISPOSAL METHOD:

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT SHIPPING NAME: NONE
DOT HAZARD CLASS: NOT DOT REGULATED

DOT LABEL(S): NONE UN/NA NUMBER: NONE PLACARDS: NONE

IATA:

NOT REGULATED BY IATA

IMO IMDG-code: NOT REGULATED FOR OCEAN TRANSPORTATION

EMS No: NA EUROPEAN CLASS: RID (OCTI): NA ADR (ECE) : RAR (IATA):

15. REGULATORY INFORMATION

SARA SECTION 302:

None Found

SARA (311,312) HAZARD CLASS:

ACUTE HEALTH HAZARD SARA (313) CHEMICALS:

NONE

CPSC CLASSIFICATION: NA

WHMIS HAZARD CLASS:

D2A VERY TOXIC MATERIALS

D2B TOXIC MATERIALS

WHMIS TRADE SECRET:

None

EXPORT:

SCHDLE B/HTSUS: 3214.10 Mastic Based on Rubber

ECCN: EAR99

HAZARD RATING SYSTEMS

HMIS FLAMMABILITY 0 , REACTIVITY 0 , HEALTH 2 NFPA FLAMMABILITY 0 , REACTIVITY 0 , HEALTH 2

CALIFORNIA PROPOSITION 65:

NONE

16. OTHER INFORMATION

This product or its components are on the European inventory of existing commercial chemicals (EINECS)..... These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. C = ceiling limit NEGL = negligible EST = estimated NF = none foundNA = not applicable UNKN = unknown
NE = none established REC = recommended
ND = none determined V = recomm. By vendor By-product = reaction byproduct, TSCA inventory
status not required under

40 CFR part 720.30(h-2)

R = recommended
R = recommended
MST = mist STEL = short term exposure NT = not tested limit

DATE PRINTED: 08/16/01